



CEWELD MA 650

TYPE	Solid welding wire for hardfacing and rebuilding wornout parts.	
ANWENDUNGEN	Rebuilding or cladding wornout parts that needs to sustain high abrasion and medium impact.	
EIGENSCHAFTEN	Solid welding wire for Hardfacing parts that are subject to high abrasion, the addition of tungsten, vanadium and molybdenum offers better cutting properties and higher hardness. Hardness: 570-660 HB	
KLASSIFIKATION	AWS	A 5.21: ERFe-8
	EN ISO	14700: S Fe8
	DIN	8555: MSG 3-GZ-60-T
	W.Nr.	1.2606
	F-nr	71

GEEIGNET FÜR Mixer blades, cutting knives, pumps, loader teeth, screws, sludge disposal, carbidge recycling etc.

ZULASSUNGEN

SCHWEISSPOSITIONEN



TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)


C	Mn	Cr	Mo	V	Fe	W
0.4	0.5	5	1.4	0.3	Rem.	1.3

MECHANISCHE GÜTEWERTE

Heat Treatment	R _{P0,2} (MPa)	R _m (MPa)	A ₅ (%)	Hardness
As Welded				60 HRc

RÜCKTROCKNUNG Not required

GAS ACC. EN ISO 14175 M21



CEWELD MA 650

MA 650 1,0MM

Packaging	KG/unit	EanCode
BS-300	15	8720663403148

MA 650 1,2MM

Packaging	KG/unit	EanCode
BS-300	15	8720663403155