

CEWELD ER 383 Tig

TYPE	ER 383 stainless steel Tig wire for GTAW welding																	
ANWENDUNGEN	Tanks and process vessels, Piping systems, agitators, rotors, cast pumps and valves for use in the fertilizer, phosphoric, sulphuric and acetic acid plants																	
EIGENSCHAFTEN	ER 383 is used to weld base metals of similar composition to itself or to other grades of stainless steel. ER383 contains a low maximum of carbon, silicon, and sulfur to decrease the hot cracking and fissuring, while maintaining the resistance to corrosion.																	
KLASSIFIKATION	AWS A 5.9: ER383 EN ISO 14343-A: W 27 31 4 Cu L W.Nr. 1.4563 F-nr 6 FM 5																	
GEEIGNET FÜR	Alloy 825 N08825 , Alloy 825 h Mo N08821, Alloy 28 and Alloy 20 (X1NiCrMoCu31-27-4), Alloy 904L (X1NiCrMoCu25-20-5), 1.4563, 1.4539, NiCr 21 Mo 2.4858, NiCr 21 Mo 6Cu 2.6410, X3NiCrCuMoTi27-23 1.4503																	
ZULASSUNGEN	CE																	
SCHWEISSPOSITIONEN	 PA  PB  PC  PD  PE  PF  PG																	
TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)	C	Si	Mn	P	S	Cr	Ni	Mo	N	Cu								
	0.02	0.4	1.55	0.017	0.01	28.2	32.1	3.9	0.05	0.95								
MECHANISCHE GÜTEWERTE	Heat Treatment As Welded			R _{P0,2} (MPa) 380		Rm (MPa) 570		A5 (%) 38	Hardness HRc									
RÜCKTROCKNUNG	Not required																	
GAS ACC. EN ISO 14175	I1, I3																	

CEWELD ER 383 Tig

ER 383 TIG 2,4 X 1000MM

Packaging	KG/unit	EanCode
Tube	5	8720682050088