



# CEWELD E DUR 25U

**TYPE** Cobalt-based thermo shock resistant alloy for overlay applications

**APPLICATIONS** Cladding valve seats, Gasturbine components. Metal working tools like piercing points, forming tools and extrusion dies that are exposed to metal on metal wear in combination with thermal fatigue. Also furnace hardware


**PROPRIÉTÉS** CEWELD E DUR 25U is a Cobalt based electrode developed to resist high impact load, high heat, thermal shock, hot corrosion, compression, abrasion, erosion and many other forms of attack. The weld deposit is machinable with carbide tools.

**CLASSIFICATION** EN ISO 14700: ~E Co1  
DIN 8555: E 20-UM-300- CTZ

**CONVIENT POUR** Valves in chemical and steam plants, Gasturbine components, Tong bits, Share blades, Hot forging and stamping tools, Hot dies, Aerospace industry, Turbo charger buckets, Hot liquid pumps etc.

**AGRÉMENTS**

**POSITIONS DE SOUDAGE**



**TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)**

C	Mn	Cr	Ni	Mo	Fe	W	Co
0.1	2	20	10	1	3	15	Rem.

**PROPRIÉTÉS MÉCANIQUES**

Heat Treatment	R <sub>P0.2</sub> (MPa)	R <sub>m</sub> (MPa)	A5 (%)	Hardness
As Welded				25 HRc

**ETUVAGE** Not required

**GAS ACC. EN ISO 14175**