



# CEWELD SP 316LSi

TYPE	Stainless steel alloy exceeding AISI 316 for corrosion protection layers.								
TOEPASSINGEN	Recommended for applications where high corrosion resistance and relatively low wear protection is required. SP 316L is good for general machine element work including hydraulic rams, rolls and for applications in the food industry.								
EIGENSCHAPPEN	Coatings of CEWELD® SP 316LSi exhibit excellent corrosion resistance against organic and non-oxidizing acids and are recommended for internal and external diameters. Using the combustion wire spray process, CEWELD® SP 316LSi should be sprayed thinner than CEWELD® SP 1.4370 and CEWELD® SP 420 coatings. Is an 316L type wire specially modified for spraying.								
CLASSIFICATIE	EN ISO 14919: X.mod type W.Nr. 1.4430								
GESCHIKT VOOR	Corrosion protection in marine environments, paper rollers etc.								
GOEDKEURINGEN									
LASPOSITIONS									
TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)	C	Si	Mn	P	S	Cr	Ni	Mo	Cu
	0.05	0.8	1.7	0.01	0.01	19	12.5	2.5	0.3
MECHANISCHE WAARDEN									
HERDROGEN	Not required								
GAS ACC. EN ISO 14175	M21								